

REFERENCES

- Altan, M. (2010). Reducing shrinkage in injection moldings via the Taguchi, ANOVA and neural network methods. *Materials and Design*, 31(1), 599–604. <https://doi.org/10.1016/j.matdes.2009.06.049>
- Angaji, M. T. (2013). SURFACE AND MECHANICAL PROPERTIES OF POLYPROPYLENE / CLAY, 19(3), 441–448. <https://doi.org/10.2298/CICEQ120226079D>
- Goodship, V. (2004). *Practical Guide to Injection Moulding*. Retrieved from http://www.dynacure.nl/download/Arburg_practical_guide_to_injection_moulding.pdf
- Groover, M. p. (2007). FUNDAMENTALS OF MODERN MANUFACTURING Materials,Processes,andSystems. <https://doi.org/10.1017/CBO9781107415324.004>
- Hilmi, M., Amin, M., & Yulis, S. (n.d.). Optimising injection moulding parameters that satisfies part qualities by using Taguchi method.
- Kamal, Z. (2007). Trouble Shooting In Plastic Injectin Molding Machines. *Public Health*, 125. <https://doi.org/10.3141/2100-07>
- Kazmer, D. O. (2016). *Injection Mold Design Engineering*.
- Mahapatra, T. R., & Panda, S. K. (2017). Characterization of Flexural Strength , Warpage and Shrinkage of Polypropylene-Nanoclay- Nanocomposites Blend with Gigantochloa Characterization of Flexural Strength , Warpage and Shrinkage of Polypropylene-Nanoclay-Nanocomposites Blend with Gigantochloa . <https://doi.org/10.1088/1757-899X/226/1/012163>
- Mehat, N. M., & Kamaruddin, S. (2011). Ac ce p te d us t. *Journal of Materials Processing Tech*. <https://doi.org/10.1016/j.jmatprotec.2011.06.014>
- Nagar, A., & Nadu, T. (2013). Optimization of Cooling Tower Performance Analysis, 17(2), 457–470. <https://doi.org/10.2298/TSCII110528024R>
- Othman, Hasan, S., Khamis, S. Z., Ibrahim, M. H. I., & Amin, S. Y. M. (2017).

- Optimisation of Injection Moulding Parameter towards Shrinkage and Warpage for Polypropylene-Nanoclay-Gigantochloa Scortechinii Nanocomposites. In *Procedia Engineering* (Vol. 184, pp. 673–680). The Author(s). <https://doi.org/10.1016/j.proeng.2017.04.137>
- Othman, M. H., Hasan, S., Nur, W., Wan, A., & Zakaria, Z. (2013). Optimising Injection Moulding Parameter Setting In Processing Polypropylene-Clay Composites through Taguchi Method, *272*, 272–276. <https://doi.org/10.4028/www.scientific.net/AMM.271-272.272>
- Othman, M. H., Hasan, S., & Wahab, S. (2014). A Review of Polypropylene Nanoclay Nanocomposites : Preparation , Properties and Applications, 944–948. <https://doi.org/10.4028/www.scientific.net/AMM.465-466.944>
- Othman, M. hilmi. (2015). The Modelling of Processing Conditions for Polypropylenenanoclay Integral Hinges At High Heat Exposure.
- Ozcelik, B. (2011). International Communication in Heat and Mass Transfer- Optimization of Injection parameters for Mechanical Properties of Specimen with Weld line of Polypropylene using Taguchi Method.
- Park, H. S., & Nguyen, T. T. (2014). Optimization of injection molding process for car fender in consideration of energy efficiency and product quality. *Journal of Computational Design and Engineering*, *1*(4), 256–265. <https://doi.org/10.7315/JCDE.2014.025>
- Pavlidou, S., & Papaspyrides, C. D. (2008). A review on polymer-layered silicate nanocomposites. *Progress in Polymer Science (Oxford)*, *33*(12), 1119–1198. <https://doi.org/10.1016/j.progpolymsci.2008.07.008>
- Scallan, P. (2002). *Process Planning : The design / manufacture interface*.
- Shahbudin, S. N. A., Othman, M. H., Amin, S. Y. M., & Ibrahim, M. H. I. (2017). A Review of Metal Injection Molding- Process, Optimization, Defects and Microwave Sintering on WC-Co Cemented Carbide. *IOP Conference Series: Materials Science and Engineering*, *226*, 12162. <https://doi.org/10.1088/1757-899X/226/1/012162>
- Sinha Ray, S., & Okamoto, M. (2003). Polymer/layered silicate nanocomposites: A review from preparation to processing. *Progress in Polymer Science (Oxford)*, *28*(11), 1539–1641. <https://doi.org/10.1016/j.progpolymsci.2003.08.002>
- Thomas, G. P. (2012). Recycling of Polypropylene (PP), 1–5. Retrieved from <https://www.azocleantech.com/article.aspx?ArticleID=240>

- Wavare, A., & Ubale, S. (2016). Parametric Investigation for PP Homopolymer (1110MAS) in Plastic Injection Molding Process using Taguchi Method. *Intro to Stats*, 4(2), 323–331.
- Wu, Y. L., Cheng, C. C., Kobayashi, M., & Yang, C. H. (2017). Novel design of extension nozzle and its application on real-time injection molding process diagnosed by ultrasound. *Sensors and Actuators, A: Physical*, 263, 430–438. <https://doi.org/10.1016/j.sna.2017.06.023>
- Yang, Y.-Ku. (2006). Optimization of injection molding process for mechanical properties of short glass fiber and polytetrafluoroethylene reinforced polycarbonate composites.
- Zakaria, Z. (2012). *THE EFFECT OF INJECTION MOLDING PARAMETERS TOWARDS THE PROCESSING OF POLYPROPYLENE-NANOCLAY COMPOSITE TEST SAMPLES IN PRACTICAL INJECTION MOLDING.*