

DAFTAR PUSTAKA

- [1] N. A. Rahman, S. Abdullah, W. F. H. Zamri, M. F. Abdullah, M. Z. Omar, and Z. Sajuri, "Ballistic limit of high-strength steel and Al7075-T6 multi-layered plates under 7.62-mm armour piercing projectile impact," *Lat. Am. J. Solids Struct.*, vol. 13, no. 9, pp. 1658–1676, 2016, doi: 10.1590/1679-78252657.
- [2] L. E. Schwer, "Preliminary Assessment of Non-Lagrangian Methods for Penetration Simulation," *8th Int. LS-DYNA Users Conf.*, no. 3.
- [3] K. Vahedi and N. Khazraiyan, "Numerical Modeling of Ballistic Penetration of Long Rods into Ceramic / Metal Armors," *8th Int. LS-DYNA Users Conf.*, pp. 39–50, 2004.
- [4] R. Vignjevic, J. Campbell, and S. Lepage, "Numerical Simulation of High Velocity Impacts on Thin Metallic Targets II," *Impact Load. Light. Struct.*, no. July, p. 49, 2004, [Online]. Available: <http://dspace.lib.cranfield.ac.uk/handle/1826/790>.
- [5] V. R., L. S., and V. T.D., "Numerical Simulation of High Velocity Impacts on Thin Metallic target I (element erosion)," *Impact Load. Light. Struct.*, no. July, p. 49, 2005.
- [6] S. Chocron, C. E. Anderson, D. J. Grosch, and C. H. Popelar, "Impact of the 7.62-mm APM2 projectile against the edge of a metallic target," *Int. J. Impact Eng.*, vol. 25, no. 5, pp. 423–437, 2001, doi: 10.1016/S0734-743X(00)00063-4.
- [7] M. Park, J. Yoo, and D. T. Chung, "An optimization of a multi-layered plate under ballistic impact," *Int. J. Solids Struct.*, vol. 42, no. 1, pp. 123–137, 2005, doi: 10.1016/j.ijsolstr.2004.07.008.
- [8] A. D. Resnyansky, "DYNA-modelling of the high-velocity impact problems with a split-element algorithm," *Int. J. Impact Eng.*, vol. 27,

- no. 7, pp. 709–727, 2002, doi: 10.1016/S0734-743X(02)00008-8.
- [9] M. A. Iqbal, K. Senthil, P. Sharma, and N. K. Gupta, “An investigation of the constitutive behavior of Armax 500T steel and armor piercing incendiary projectile material,” *Int. J. Impact Eng.*, vol. 96, pp. 146–164, 2016, doi: 10.1016/j.ijimpeng.2016.05.017.
 - [10] P. J. Hazell, *Armour: Materials, Theory, and Design*. 2015.
 - [11] R. L. Woodward, “A simple one-dimensional approach to modelling ceramic composite armour defeat,” *Int. J. Impact Eng.*, vol. 9, no. 4, pp. 455–474, 1990, doi: 10.1016/0734-743X(90)90035-T.
 - [12] V. G. Reyes and W. J. Cantwell, “The high velocity impact response of composite and FML-reinforced sandwich structures,” *Compos. Sci. Technol.*, vol. 64, no. 1, pp. 35–54, 2004, doi: 10.1016/S0266-3538(03)00197-0.
 - [13] B. S. Ünlü and E. Atik, “Determination of friction coefficient in journal bearings,” *Mater. Des.*, vol. 28, no. 3, pp. 973–977, 2007, doi: 10.1016/j.matdes.2005.09.022.
 - [14] V. mises Ansys, “Equivalent Stress - Ansys,” vol. 2, no. December, p. 2020, 2020.
 - [15] S. Barrett, R. V. L. R. Christiansen, and A. Othman, “BALLISTIC PROPERTIES OF PROJECTILE MATERIAL,” 2016.
 - [16] S. Barrett, “Ballistic Properties of,” 2016.
 - [17] Z. Zhao *et al.*, “Experiments and simulations,” *Ceram. Int.*, 2020, doi: 10.1016/j.ceramint.2020.06.162.