

**DESIGN 10 STORY HOSPITAL BUILDING IN KLATEN WITH DIRECT
DISPLACEMENT BASED DESIGN METHOD**

Final Project

final project as part of
Civil Engineering Bachelor Degree requirement



Submitted by:

Atthariq Praszita

Student Number: D100 164 005

For:

**CIVIL ENGINEERING DEPARTMENT ENGINEERING FACULTY
UNIVERSITAS MUHAMMADIYAH SURAKARTA**

2023

APPROVAL SHEET
DESIGN 10 STORY HOSPITAL BUILDING IN KLATEN WITH DIRECT
DISPLACEMENT BASED DESIGN METHOD

Final Project

Submitted and tested by the Board of Examiners in Faculty of Engineering
Universitas Muhammadiyah Surakarta on August 9th 2023

Submitted by:

ATTHARIO PRASZITA

Student Number: D100 164 005

Board of Examiners

Supervisor



Ir. Mochamad Solikin, S.T., M.T., Ph.D.
NIDN: 0617127201

Examiner I



Ir. Budi Setiawan, S.T., M.T.
NIDN: 0622056901


Examiner II



Ir. Yenny Nurchasanah, S.T., M.T.
NIDN: 0631037701

This Final Project is accepted as a requirement
to achieve Civil Engineering Bachelor Degree Requirement
Surakarta, August 9th 2023

Dean of the Engineering Faculty,



Ir. Rois Fatoni, S.T., M.Sc. Ph.D.
NIDN: 0603027401

Head of Civil Engineering Department,



Ir. Anto Bud Listvawan, S.T., M.Sc.
NIDN: 0622036101

DECLARATION of AUTHORSHIP

Name : ATTHARIQ PRASZITA
Student Number : D100164005
Faculty/Department : ENGINEERING/CIVIL ENGINEERING
Title of Final Project : DESIGN 10 STORY HOSPITAL BUILDING IN
KLATEN WITH DIRECT DISPLACEMENT BASED
DESIGN METHOD

I hereby certify that this final project has been composed by me and is based on my own work, unless stated otherwise. No other person's work has been used without due acknowledgement in this final project. All references and verbatim extracts have been quoted, and all sources of information, including graphs and data sets, have been specifically acknowledged. This paper was not previously presented to another examination board and has not been published.

Surakarta, August 9th 2023

Author,



(Atthariq Praszita)

PREFACE

Assalamu'alaikum Wr. Wb.

Alhamdulillah, all praise to Allah SWT who has given blessing and mercies until this Final Project can be completed. This Final Project is to complete the requirement to achieve Bachelor of Engineering degree in Civil Engineering, Engineering Faculty, Universitas Muhammadiyah Surakarta. The author also says thank you to all parties below who has given support in completion of this Final Project:

1. Beloved family, Father, Mother, Brother, Sister, and Nephews. Thank you for all the prayers, support, love, and affection you have given to me throughout these years.
2. Mr. Ir. Rois Fatoni, S.T., M.Sc., Ph.D., as the Dean of Engineering Faculty, Universitas Muhammadiyah Surakarta.
3. Mr. Ir. Anto Budi Listyawan, S.T., M.Sc., as Head of Civil Engineering Department, Universitas Muhammadiyah Surakarta.
4. Mrs. Ir. Renaningsih, M.T., as an academic advisor who has given an academic advice and support for author.
5. Mr. Ir. Mochamad Solikin, S.T., M.Sc., Ph.D., as author's final project advisor who has given many suggestions and endless support for author.
6. Mr. Ir. Budi Setiawan, S.T., M.T., as first examiner who has given a lot of advice to make this final project better.
7. Mr. Ir. Yenny Nurchasanah, S.T., M.T., as second examiner who has given a lot of advice to make this final project better.
8. All lecturers in Civil Engineering Department, Universitas Muhammadiyah Surakarta thank you for your guidance, lesson and knowledge.
9. All my friend from Civil Engineering Study Program, thank you for everything.
10. All parties that cannot be mentioned one by one who have helped to accomplishing this Final Project.

The author realizes that this Final Project is not perfect one. Because of that, the author hope for any suggestion and criticism to make this Final Project better.

Wassalamu'alaikum Wr. Wb.

Surakarta, August 9th 2023

Author

TABLE OF CONTENTS

TITLE PAGE	i
APPROVAL SHEET	ii
DECLARATION of AUTHORSHIP	iii
PREFACE	iv
TABLE OF CONTENTS	v
LIST OF FIGURES	ix
LIST OF TABLES	xii
CHAPTER I PRELIMINARY	1
A. Background	1
1. Problem formulation	1
2. Final project authenticity	2
3. Problem limitation	2
B. Objective and Benefit of Final Project	3
1. Objective	3
2. Benefit	3
CHAPTER II LITERATURE REVIEW	4
A. General	4
B. Design using Direct Displacement Based Design	4
CHAPTER III BASIC THEORY	6
A. Structure Performance	6
1. Structure performance point ATC-40 method	9
2. Deformation limit	10
B. Designing Step and Method	11
CHAPTER IV METHODOLOGY	16
A. Design Data	16
B. Software for Design	16

C.	Code.....	17
D.	Design Stage.....	17
CHAPTER V STRUCTURE ANALYSIS		19
A.	Configuration and Structure Load.....	19
1.	Design data	19
2.	Gravitation load	19
3.	Earthquake lateral load for dual system structure (x-x).....	20
4.	Earthquake lateral load for dual system structure (y-y).....	35
B.	Structure Modelling.....	50
C.	Structure Irregularities Check	56
1.	Horizontal structure irregularity check	56
2.	Vertical structure irregularity check	62
D.	Structure Overturning Analysis.....	72
CHAPTER VI SLAB DESIGN		75
A.	Roof Slab Design.....	75
1.	Roof slab plan	75
2.	Design data	76
3.	Load analysis	76
4.	Slab moment calculation.....	76
5.	Roof slab reinforcement calculation	77
B.	Floor Slab Design.....	85
1.	Floor slab plan	85
2.	Design data	86
3.	Load analysis	86
4.	Calculation of slab moment	87
5.	Floor slab reinforcement calculation	89

C.	Ramp Slab Design	99
1.	Ramp slab plan.....	99
2.	Design data	99
3.	Load analysis	100
4.	Slab moment calculation.....	100
5.	Ramp slab reinforcement analysis	101
D.	Secondary Beam Analysis.....	109
1.	Beam dimension adequacy control	109
2.	Longitudinal reinforcement	110
3.	Transversal reinforcement	115
CHAPTER VII BEAM, COLUMN, JOINT, AND SHEAR WALL DETAILING		118
A.	Beam Design	118
1.	Beam reinforcement.....	118
2.	Confinement bar	125
B.	Column Design.....	136
1.	Column interaction diagram	136
2.	Column reinforcement	141
C.	Joint Design.....	158
1.	Horizontal transversal bar calculation	159
2.	Vertical transversal bar calculation.....	161
D.	Shear Wall	162
1.	Shear wall design diagram.....	162
2.	Shear wall reinforcement	166
CHAPTER VIII PERFORMANCE EVALUATION AND ASSESSMENT		175
A.	Nonlinear Static Pushover Analysis	175

1.	Capacity curve	175
2.	Structure plastification mechanism.....	177
B.	Structure Performance Evaluation.....	185
C.	Assessment	189
CHAPTER IX CLOSING		194
A.	Conclusion.....	194
B.	Suggestion	194
REFERENCES.....		195
ATTACHMENT		

LIST OF FIGURES

Figure III.1. Typical Curve of Structure Performance Level.....	7
Figure III.2. Structure Performance at The Structure Damping Level	10
Figure III.3. Displacement Spectrum (Source: Prietsley)	14
Figure IV.1. Design Stage Flowchart.....	18
Figure V.1. Elastic Response Spectrum Design.....	22
Figure V.2. Relative Overturning Moment	27
Figure V.3. Spectra Displacement on the 8,4% Damping	34
Figure V.4. Elastic Response Spectrum Design.....	37
Figure V.5. Relative Overturning Moment	42
Figure V.6. Spectra Displacement on The 7,19% Damping.....	49
Figure V.7. 3D Model of the Structure	51
Figure V.8. Model Cross Section at Grid A.....	51
Figure V.9. Model Cross Section at Grid B	52
Figure V.10. Model Cross Section at Grid C	52
Figure V.11. Model Cross Section at Grid D.....	53
Figure V.12. Model Cross Section at Grid 1.....	53
Figure V.13. Model Cross Section at Grid 2.....	54
Figure V.14. Model Cross Section at Grid 5.....	54
Figure V.15. Model Cross Section at Grid 6.....	55
Figure V.16. Model Plan on the 1 st -9 th floor	55
Figure V.17. Model Plan on the 10 th floor	56
Figure V.18. Torsion illustration on the building	56
Figure V.19. Building torsion check on the X direction quake	57
Figure V.20. Building torsion check on the Y direction quake	57
Figure V.21. Horizontal Irregularities 1a and 1b X Direction	58
Figure V.22. Horizontal Irregularities 1a and 1b Y Direction	59
Figure V.23. Illustration of inner corner irregularity check.....	59
Figure V.24. Illustration of irregularity shift transverse due to area.....	60
Figure V.25. Illustration of non-parallel system irregularity	61

Figure V.26. Illustration of soft story stiffness irregularity check.....	63
Figure V.27. Vertical Irregularity 1a and 1b X Direction.....	64
Figure V.28. Vertical Irregularity 1a and 1b Y Direction.....	65
Figure V.29. Illustration of mass irregularity checks.....	65
Figure V.30. Mass Irregularity.....	66
Figure V.31. Drift Ratio Check.....	68
Figure V.32. Illustration of vertical geometric irregularity.....	69
Figure V.33. Discontinuity inner area direction irregularity checking on a vertical lateral force retaining	69
Figure V.34. Lateral Strength Irregularity X Direction	71
Figure V.35. Lateral Strength Irregularity Y Direction	71
Figure VI.1. Roof slab plan for 10 th story	75
Figure VI.2. Roof slab plan for topping plan.....	75
Figure VI.3. Floor slab plan for 2 nd until 10 th stories	86
Figure VI.4. Floor slab plan for 11 st stories	86
Figure VI.5. Ramp slab plan for as 1 and 2	99
Figure VI.6. Ramp slab plan for as 9 and 10.	99
Figure VII.1. Beam plan on 1 st -9 th floor.....	118
Figure VII.2. Cover moment Beam B69.....	125
Figure VII.3. The ultimate shear force (kN) on the left edge	129
Figure VII.4. The ultimate shear force (kN) outside plastic hinge left edge	129
Figure VII.5. The ultimate shear force (kN) on the right edge	129
Figure VII.6. The ultimate shear force (kN) outside plastic hinge right edge	129
Figure VII.7. Engineering drawing beam B69 on 2 nd floor	135
Figure VII.8. Reviewed column building plan.....	136
Figure VII.9. Column design diagram	141
Figure VII.10. Column design diagram	143
Figure VII.11. 2 nd floor C16 column reinforcement	145
Figure VII.12. Column design strength interaction diagram 32D22 X direction	152
Figure VII.13. Confinement bar of the column C16 2 nd floor	158
Figure VII.14. Joint position	159

Figure VII.15. Reinforcement joint J22 at 2 nd floor.....	161
Figure VII.16. Location of reviewed shear walls analysis.....	162
Figure VII.17. Reviewed shear wall cross section.....	163
Figure VII.18. Shear wall design diagram	166
Figure VII.19. Shear wall reinforcement at the story-3 and story-4	169
Figure VII.20. Shear wall reinforcement at the story-2	169
Figure VII.21. Wall strength design interaction diagram	171
Figure VII.22. Shear wall reinforcement at the story-1 outside plastic hinge	173
Figure VII.23. Shear wall reinforcement at the story-1 inside plastic hinge area	174
Figure VIII.1. The plastic hinge element plastification level.....	176
Figure VIII.2. Pushover x step-0.....	178
Figure VIII.3. Pushover x step-1	178
Figure VIII.4. Pushover x step-2.....	179
Figure VIII.5. Pushover x step-3.....	179
Figure VIII.6. Pushover x step-4.....	180
Figure VIII.7. Pushover x step-5.....	180
Figure VIII.8. Push y Step 0 and Step 1.....	181
Figure VIII.9. Push y Step 2 and Step 3.....	182
Figure VIII.10. Push y Step 4 and Step 5.....	182
Figure VIII.11. Push y Step 6 and Step 7.....	183
Figure VIII.12. Decision Variables Due to FEMA 273/356 Performance Level	183
Figure VIII.13. The capacity curve x-x direction	184
Figure VIII.14. Pushover binary curve x-x direction.....	186
Figure VIII.15. Pushover binary curve x-x direction.....	187
Figure VIII.16. Drift Comparison x-x Direction	190
Figure VIII.17. Displacement Comparison x-x Direction	191
Figure VIII.18. Drift Comparison y-y Direction	192
Figure VIII.19. Displacement Comparison y-y Direction	193

LIST OF TABLES

Table III.1. Building Performance After Shock by an Earthquake.....	7
Table V.1. Gravitation loading design on the structure	20
Table V.2. Acceleration response design.....	21
Table V.3. Effective seismic mass	22
Table V.4. Base shear of the shear wall at x-x direction.....	23
Table V.5. Relative Overturning Moment Calculation.....	27
Table V.6. Designated displacement design profile.....	29
Table V.7. Spectra displacement on 8,4% damping calculation.....	32
Table V.8. Shear Force Distribution on Each Story x-x Direction	35
Table V.9. Acceleration response design.....	37
Table V.10. Effective seismic mass	38
Table V.11. Base shear of the shear wall at y-y direction.....	38
Table V.12. Relative Overturning Moment Calculation.....	42
Table V.13. Designated displacement design profile.....	44
Table V.14. Spectra displacement on 7,19% damping calculation.....	48
Table V.15. Shear Force Distribution on Each Story y-y Direction	50
Table V.16. Torsion check on the X direction quake	57
Table V.17. Torsion check on the X direction quake	58
Table V.18. The result of horizontal structure irregularity	61
Table V.19. Checking Soft Story Stiffness Irregularity X Direction.....	63
Table V.20. Checking Soft Story Stiffness Irregularity Y Direction.....	64
Table V.21. Mass irregularity checking	66
Table V.22. Check ratio drift X direction	67
Table V.23. Check ratio drift X direction	67
Table V.24. Lateral strength irregularity X direction	70
Table V.25. Lateral strength irregularity Y direction	70
Table V.26. The result of horizontal structure irregularity	72
Table V.27. Distribution of Quake Force on Each Story	73
Table V.28. Overturning Analysis of the Structure	73

Table VI.1. Moment on the roof slab	77
Table VI.2. Roof slab moment and reinforcement design	85
Table VI.3. Moment on the floor slab	87
Table VI.4. Floor slab moment and reinforcement design	96
Table VI.5. Moment on the ramp slab.	100
Table VI.6. Ramp slab moment and reinforcement design	108
Table VII.1. Determining number of M_u at beam B69 on the 2 nd floor	119
Table VII.2. Calculated beam ultimate shear force due to Clause 21.6.2.2	128
Table VII.3. Hoop spacing correction on the beam B69 2 nd floor due to the torsion effect	134
Table VII.4. Installed longitudinal reinforcement primary beam B69 on 2 nd floor	135
Table VII.5. Q and R value to making a column design diagram	140
Table VII.6. Envelope P_u and M_u on the column C16 on 2 nd floor	142
Table VII.7. Column moment capacity 2 nd floor C16	154
Table VIII.1. Output pushover x-x direction	175
Table VIII.2. Output pushover y-y direction	176
Table VIII.3. Deformation Limit Due to Performance Level	188
Table VIII.4. Performance Point Comparison	188
Table VIII.5. Drift Value and Displacement Comparison x-x Direction	190
Table VIII.6. Drift Value and Displacement Comparison y-y Direction	191

NOTATIONS

f_u	: Steel ultimate stress, MPa
f'_c	: Concrete quality, MPa
f_y	: Steel yield strength, MPa
f_{ye}	: Reinforcement effective yield strength, MPa
g	: Gravity acceleration, 9.81 m/sec ²
H_{cf}	: Height of wall contraflexure
H_e	: Effective height, m
H_{i+1}	: Height at level i+1, m
H_i	: Height at level i, m
H_n	: Structure height at the level of-i, m
L_b	: Clear length of the structure beam, m
L_p	: Plastic hinge length, m
L_{sp}	: Strain penetration length to foundation, m
L_w	: Shear wall length, m
k	: Constanta
K_e	: Lateral effective stiffness, kN/m
Ke	: System effective stiffness, kN/m
K_i	: Elastic lateral stiffness, kN/m
m_e	: Effective mass
m_i	: Story mass at the level of-i
M_{OTM}	: Total overturning moment at the structure base

$M_{OTM,F}$	: Total overturning moment at the frame
$M_{OTM,i}$	: Total overturning moment at the level of-i
$M_{w,i}$	: The unit of moment that occurs at the height of level i
M_{wI+1}	: The unit of moment that occurs at the height of level i+1
n	: Number of stories
R	: Necessary elastic strength ratio due to calculated yield strength
R_{ζ}^{χ}	: Spectra displacement correction factor at the damping level
S_a	: Spectra acceleration, g
S_d	: Spectra displacement, m
T	: Fundamental period, second
T_e	: Effective period, second
T_0	: Characteristic period which getting from response spectrum curve
T_1	: Elastic period, second
V	: Base shear, kN
V_{Base}	: Total base shear, kN
V_F	: Frame base shear, kN
V_i	: Total shear force at the level of-i, kN
V_w	: Shear wall base shear, kN
V_y	: Base shear when the structure yield, kN
V_{wi+1}	: The unit of shear force that occurs at the height of i + 1
W	: Structure weight, Kn
$w_{i/g}$	: Mass at the level of-i

α_l	: Modal coefficient mass at the first mode
β_{eq}	: Structure viscous damping equivalent, %
β_F	: Frame shear force ratio, %
β_o	: Hysteretic damping which represent viscous equivalent, %
δ_T	: Displacement target, m
Δ_{yi}	: Yield displacement profile, m
Δ_{Di}	: Displacement design profile, m
Δ_i	: Drift at the level of-i, m
Δ_{roof}	: Roof drift, m
Δ_{yW}	: Yield drift at the shear wall when reach the effective height
ε_y	: Reinforcement strain at the beam (f_{ye}/E)
θ_{cF}	: Drift at the contraflexure height, H_{CF}
θ_c	: Drift limit
μ_F	: Ductility displacement of the frame system
μ_{Sys}	: Ductility displacement of the system
μ_w	: Ductility displacement of the shear wall
ζ_{eq}	: Equivalent viscous damping, %
ζ_{el}	: Initial elastic damping 5% ordinary value
ζ_f	: Effective concrete frame damping, %
ζ_{hyst}	: Hysteretic damping from the structure system, %
ζ_w	: RC-Walll effective damping, %
ϕ_{yW}	: Yield curvature, /m

φ_{il} : Mode-1 amplitude at the level of-i

$\omega\theta$: Correction factor

DESIGN 10 STORY HOSPITAL BUILDING IN KLATEN WITH DIRECT DISPLACEMENT BASED DESIGN METHOD

Atthariq Praszita

Civil Engineering Department, Faculty of Engineering, Universitas Muhammadiyah Surakarta, Jl. A. Yani, Pabelan, Kartasura, Sukoharjo, Jawa Tengah 57169 Indonesia.

Corresponding author: atthariqpraszita@gmail.com

Abstract

Indonesia as a country located inside ring of fire made this country have prone to earthquake. It forced the structure engineer to build design as efficient as possible to resulting the adequate building design. Direct Displacement Based Design (DDBD) is a method which developed as an alternative to design the structure as efficient due to the performance of the building. This final project was designing 10 stories hospital building located in Klaten, Central Java, Indonesia. The structure using dual system structure and stand above the middle soil classification. The applied earthquake loads in the building conduct by Direct Displacement Based Design method then detailing by SNI 2847:2013 code. The design evaluated by conducting Nonlinear Static Pushover Analysis to acknowledge the performance according to FEMA 440. The result shows that the performance point of the structure is on immediate occupancy and meet the hospital design criteria. Drift result showing 0,004 for x direction and 0,005 for y direction. According to deformation limit at Table 11 – 4, ATC-40 for hospital building importance, performance target only allows on immediate occupancy level, which the maximum inelastic drift is 0,005. Due to the inelastic drift result, the structure meets the design criteria for Immediate Occupancy performance level on X and Y direction.

Keywords: DDBD, Nonlinear Static Pushover, Seismic Engineering, Engineering